

## Guaranteed Technical Particulars

Doc.No: M/GTP/Traction Power/36V 336Ah

**MICROTEX**<sup>®</sup>

### Battery Particulars

· Manufacturer's name & Address	: Microtex Energy P. Ltd. #42 & 43, 2nd Main, 2nd Phase, Peenya Industrial Area, Bangalore – 560058
· Battery Type	: Microtex Traction Power Lead Acid Tubular Battery
· Battery Rating	: 36V-336Ah to 1.70 ECV @ C5 at 30°C
· Manufacturers Model No	: 8 MIPzB 336
· No of Cells	: 18 Nos.
· Cell dimensions	: 141x158x359 mm
· Battery bank dimensions	: 1000x474x400 mm

### Charge Regime

	: Batteries shall be charged in constant potential mode with current limit.
· Normal charging Current	: 34 Amps
· Maximum charging Current	: 68 Amps
· Recommended Voltage Compensation	: For every 1°C raise in temperature reduce the float voltage by 0.003VPC

### Product Details

· Self Discharge/month @ 27°C	: 2% of rated capacity
· Operational Temperature	: -20°C to 45°C, Recommended 10°C to 35°C Short Time 45°C to 55°C
· Recommended Max period of storage	: 6 Months from the date of manufacturing and the batteries shall be stored in covered area at 27°C
· Material of container	: Polypropylene co-polymer Fire Retardant
· Type of separator	: Polyethylene(PE)
· Type of +ve & -ve plates	: Positive: Tubular Negative :Flat pasted
· Material of tray	: Mild steel coated with acid resistant powder coating
· Method of connection between cells	: welded
· Voltage ripple allowable	: < 2% of the RMS Value
· Type of connectors	: Lead inter cell connector
· Depth of Discharge	: Max. 80% at 30 Deg C

### Applicable Standards

· Batteries generally conforms to:	: IS 5154 (Part 1) 2013
	: IEC 60254-1:2005
	: IEC 254-2
	: EN 60 254-2

[info@microtex.in](mailto:info@microtex.in)

[www.microtexindia.com](http://www.microtexindia.com)